

MAVERICK

MATERIAL HANDLING

MAVERICK TELEHANDLERS PRODUCT RANGE



www.maverickmth.com



sales@maverick-americas.com



USA
+1 786.340.6550



LATIN AMERICA
+56 926.434.876



NORTH AMERICA
310 Edgewood Lane,
Cleburne, Texas 76031 - USA



LATIN AMERICA
Avenida Presidente Kennedy
Nro. 5.600, Of. 507,
Vitacura, Santiago de Chile

AGRICULTURE

Reliable performance for every agricultural application.

MVT7.22



	<i>Imperial</i>	<i>Metric</i>
Engine Power (Kubota)	70.5 hp	52.6 kW
Max Lift Capacity	7,055 lb	3,200 kg
Max Lift Height	22 ft	6.70 m
Operational Weight	14,495 lb	6,575 kg
Max Forward Reach	12.07 ft	3,680 mm

MVT9.24



	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	121 hp	90 kW
Max Lift Capacity	7,720 lb	4,300 kg
Max Lift Height	23.5 ft	7.15 m
Operational Weight	20,000 lb	9,070 kg
Max Forward Reach	13.37 ft	4,075 mm

MVT9.32



	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	121 hp	90 kW
Max Lift Capacity	8,820 lb	4,000 kg
Max Lift Height	31.7 ft	9.65 m
Operational Weight	19,765 lb	8,965 kg
Max Forward Reach	23.03 ft	7,020 mm

MVT5519



	<i>Imperial</i>	<i>Metric</i>
Engine Power (Kubota)	70.5 hp	52.6 kW
Max Lift Capacity	5,510 lb	2,500 kg
Max Lift Height	19.20 ft	5.90 m
Operational Weight	10,640 lb	4,825 kg
Max Forward Reach	11.1 ft	3,380 mm

Built for demanding jobsites. Engineered for strength, reach, and productivity.

MVT13.27



	Imperial	Metric
Engine Power (Cummins)	121 hp	90 kW
Max Lift Capacity	13,230 lb	6,000 kg
Max Lift Height	27.3 ft	8.30 m
Operational Weight	25,850 lb	11,725 kg
Max Forward Reach	14.76 ft	4,500 mm

MVT9.32



	Imperial	Metric
Engine Power (Cummins)	121 hp	90 kW
Max Lift Capacity	8,820 lb	4,000 kg
Max Lift Height	31.7 ft	9.65 m
Operational Weight	19,765 lb	8,965 kg
Max Forward Reach	23.03 ft	7,020 mm

MVT10.45



	Imperial	Metric
Engine Power (Cummins)	121 hp	90 kW
Max Lift Capacity	9,920 lb	4,500 kg
Max Lift Height	45 ft	13.70 m
Operational Weight	27,645 lb	12,540 kg
Max Forward Reach	30.35 ft	9,250 mm

MVT5519



	Imperial	Metric
Engine Power (Kubota)	70.5 hp	52.6 kW
Max Lift Capacity	5,510 lb	2,500 kg
Max Lift Height	19.20 ft	5.90 m
Operational Weight	10,640 lb	4,825 kg
Max Forward Reach	11.1 ft	3,380 mm

CONSTRUCTION - EXTENDED REACH



MVT10.56

	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	121 hp	90 kW
Max Lift Capacity	9,920 lb	4,500 kg
Max Lift Height	55.5 ft	16.90 m
Operational Weight	31,250 lb	14,175 kg
Max Forward Reach	41.5 ft	12,650 mm

MVT12.58

	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	134 hp	100 kW
Max Lift Capacity	12,120 lb	5,500 kg
Max Lift Height	58 ft	17.60 m
Operational Weight	32,860 lb	14,905 kg
Max Forward Reach	43.98 ft	13,100 mm



MVT13.27

	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	121 hp	90 kW
Max Lift Capacity	13,230 lb	6,000 kg
Max Lift Height	27.3 ft	8.30 m
Operational Weight	25,850 lb	11,725 kg
Max Forward Reach	14.76 ft	4,500 mm



MVRT11.68

	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	121 hp	90 kW
Max Lift Capacity	11,025 lb	5,000 kg
Max Lift Height	67.6 ft	20.60 m
Operational Weight	38,745 lb	17,575 kg
Max Forward Reach	58.4 ft	17,800 mm



MVRT13.81

	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	154 hp	115 kW
Max Lift Capacity	13,230 lb	6,000 kg
Max Lift Height	81 ft	24.70 m
Operational Weight	44,590 lb	20,225 kg
Max Forward Reach	70.21 ft	21,400 mm

MVRT15.114

	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	173 hp	129 kW
Max Lift Capacity	15,435 lb	7,000 kg
Max Lift Height	114 ft	34.70 m
Operational Weight	53,405 lb	24,225 kg
Max Forward Reach	91.86 ft	28,000 mm



MINING

Engineered for the toughest underground and open-pit applications.



MVT7.22

	<i>Imperial</i>	<i>Metric</i>
Engine Power (Kubota)	70.5 hp	52.6 kW
Max Lift Capacity	7,055 lb	3,200 kg
Max Lift Height	22 ft	6.70 m
Operational Weight	14,495 lb	6,575 kg
Max Forward Reach	12.07 ft	3,680 mm

MVT9.32

	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	121 hp	90 kW
Max Lift Capacity	8,820 lb	4,000 kg
Max Lift Height	31.7 ft	9.65 m
Operational Weight	21,955 lb	9,960 kg
Max Forward Reach	23.03 ft	7,020 mm



MVT12.58

	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	134 hp	100 kW
Max Lift Capacity	12,120 lb	5,500 kg
Max Lift Height	58 ft	17.60 m
Operational Weight	32,860 lb	14,905 kg
Max Forward Reach	43.98 ft	13,100 mm

MVT13.27



	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	121 hp	90 kW
Max Lift Capacity	13,230 lb	6,000 kg
Max Lift Height	27.3 ft	8.30 m
Operational Weight	26,710 lb	12,115 kg
Max Forward Reach	14.76 ft	4,500 mm

MVHT30.32

	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	173 hp	129 kW
Max Lift Capacity	29,765 lb	13,500 kg
Max Lift Height	31.5 ft	9.60 m
Operational Weight	45,360 lb	20,575 kg
Max Forward Reach	17.06 ft	5,200 mm



MVHT35.32

	<i>Imperial</i>	<i>Metric</i>
Engine Power (Cummins)	173 hp	129 kW
Max Lift Capacity	35,275 lb	16,000 kg
Max Lift Height	31.5 ft	9.60 m
Operational Weight	47,565 lb	21,575 kg
Max Forward Reach	17.06 ft	5,200 mm

MAVERICK

COMPANY PROFILE



ENGINEERED IN TEXAS. DEPLOYED WORLDWIDE

With a dealer network spanning USA, Europe, Asia, Southeast Asia and Latin America.

Team: 100+ dedicated employees.



PRODUCT RANGE

- ▶ **Versatility:** Over 20 distinct models available.
- ▶ **Performance:** Load capacities from 5,000 lb to 55,000 lb and lifting heights from 20 ft to 115 ft.
- ▶ **Applications:** Engineered for Agriculture, Construction, Underground Mining and open pit.



USA: +1 786.340.6550



Latin America: +56 926.434.876



Website: www.maverickmth.com



Email: sales@maverick-americas.com



NORTH AMERICA

310 Edgewood Lane
Cleburne, Texas 76031 - USA



LATIN AMERICA

Avenida Presidente Kennedy Nro. 5.600,
Of. 507, Vitacura, Santiago de Chile