

Telehandler

Rotating Telehandlers



MAVERICK

7200 White
St. Fort Worth TX 76135
United States

+1 786.340.6550
www.maverickmth.com

Load Chart

Outrigger Up



Outrigger Up



Machine Parameters

MODELS		MVRT5018	MVRT6025
System	Measurements	Metric	
Machine Parameters	Max. Lift Capacity	5000kg	6,000kg
	Max, Lift Height	17800mm	24,700mm
	Overall Length	6050/7450mm	7,955/9,360mm
	Overall Width	2,500mm	2,500mm
	Overall Height	3100mm	3,150mm
	Max. Outreach at Max Height	2750mm	-
	Max. Working Distance	15100mm	21,290mm
	Weight	14500kg	20,150kg
	Ground Clearance	330mm	400mm
	Min. Turning radius	4200mm	4,400mm
	Driving Speed	35km/h	
	Grade Ability	40%	35%
Power System	Power Source	Cummins QSF 3.8	
	Emissionstander	Euro V	
	Rated power	90kW	115kW
	Max. Torque	500Nm/1,500rpm	620Nm/1,500rpm
Driving System	Driving mode	Hydrostatic Drive	
	Driving	4x4	
	Steering Mode	2ws, Crab Steer, 4ws	
	Tires	445/65-22.5 / 405/70-24	445/65-22.5-20PR-TL
Tank Capacity	Fuel Tank Capacity	150L	280L
	Hydraulic Oil Capacity	180L	300L
Keyparts Configuration	Engine	Cummins	
	Axle	Carraro	
	Hydraulic pump	Hengli/Inline	
	Multiplex valve	Husco	
	Cab	Closed,AC,LED lights	
	Attachment	48in Fork	